

## LAND Loaders




- Designed, tested, and manufactured in the USA
- Powder coat paint in tractor matching colors
- 2 year loader frame warranty
- High strength materials utilized throughout
- Oval cross tube increases strength and weld inches
- Large radius side plates for modern appearance and strength
- Quick easy dismounting, position parking stands, pull 2 pins, and park
- Mounting bracket design enhances visibility when loader is parked
- Grease fittings conveniently located for quick lubrication
- American Standard Threads used on all base loader hoses and fittings for easy serviceability


## **Skid Steer Tool Carrier**

The KMW 1220 comes with Skid Steer Quick Attach










A	Maximum Lift Height to Pivot Point	10' 4"
C	<b>Clearance with Bucket Fully Dumped</b>	8' 2"
D	Reach at Maximum Lift Height	2' 2"
	Maximum Dump Angle	40°
F	Reach with Bucket on Ground	6' 1"
G	Maximum Rollback Angle	17°
Н	Digging Depth	5.5"
U	Lift Capacity to Maximum Height at Pivot Pin	3,609#
V	Lift Capacity to Maximum Height at 31.5" Forward	2,406#
Y	Breakout Force at Ground Line at Pivot Pin	5,340#
Z	Breakout Force at Ground Line at 31.5" Forward	3,596#
	Hydraulic Pressure	2950 psi

Specifications based on ASAE standards S301.3 and furnished for general information only as they can vary with different tractor models. Specifications are subject to change without notice, and without liability therefore.



## **KMW GETS THE STRESS OUT!**

The less red you see...the less stress there is. This Finite Element Analysis confirms that KMW Mounting Kits are designed to maximize strength and loader performance compared to the competition. That's another reason KMW loaders are more rugged and last longer.

KMW Ltd. 198 N. Highway 281 Great Bend, KS 67530 620-793-6725 Fax 620-793-6737

Toll Free 855-456-9583 www.kmwloaders.com